ACCESSORY

AMARU Deheater

Ducts the AMARU's exhaust heat out of the room, or into a room you want to warm. Magnetic mount, 12 V.



TYPE	PRICE (FROM, EX-VAT)
Deheater	€160

Why choose the Deheater

- **Protects drying performance**: Removes exhaust heat before it raises room temperature and forces the refrigeration circuit to work harder.
- **Cooler, more comfortable workspace**: Pulls waste heat out of kitchens and production rooms instead of letting it pool around the operator.
- **Installs in minutes**: Magnetic mount, no modification to the AMARU, runs on 12 V at negligible power draw.
- **Extends equipment life**: Lower ambient heat means less thermal stress on the compressor and electronics over their service life.
- **Free heat you can reuse**: Redirects up to 1.5 kW (≈5,000 BTU/h) of waste heat into an adjacent room, store or greenhouse instead of wasting it.

TECHNICAL SPECIFICATIONS

Compatibility	**AMARU 5/7/5 Double/7 Double**
Type	**Deheater**

+34 614 332 324 team@freeze-drying.tech freeze-drying.tech

Scan for current specifications and prices, or to request a quotation.

Specifications are provided by the manufacturer and are subject to change without notice. Figures are for planning purposes; confirmed values are provided per quotation. Metric units.